

## KCS-TF3/PI-230/3

| Hose Capacity (in)  |           | Motor Strength (HP) |
|---------------------|-----------|---------------------|
| 1 – 2 Wire          | 3         |                     |
| 4 SP / 6 SP         | 2 1/2 / 2 | 76                  |
| Industrial          | 2 1/2     | 7.5                 |
| Max opening (mm)    | 100       |                     |
| Cutter Size         |           |                     |
| L x W x H (in)      |           | 40.4 x 27.6 x 45.3  |
| Weight (lbs)        |           | 530                 |
| Blade Diameter (mm) |           | 400                 |
|                     |           |                     |
| Part Number         |           | Motor Info          |
| KCS-TF3/PI-230/3    |           | 7.5 HP (230 V) 3 PH |

Description: A stand alone unit ideal for cutting 2" six spiral hydraulic hose. The blade is recessed inside the base for additional safety. Uses 100 PSI pneumatic input control.

Suggested for use with KC3-H135 series crimpers.



## **Included Accessories:**



Enclosed Blade Chamber



Ventilation Port\*




Serrated Blade **BLADE-SER400** 

\* Separate suction device required for fume extraction

## **Optional Accessories:**





Centering & Measuring Device CENTER-KCS

Measuring Hose Tray TRAY-KCS



Stroke Counter STROKE-KCS



**BLADE-SMT400** 

Smooth Blade

**Diamond Blade BLADE-DIA400** 

Because we continually examine ways to improve our products, we reserve the right to alter specifications or discontinue products without prior notice.

