

# Service Crimper Comparison



**KC1-H47E**



**KC1-H47PM**



**KC1-H47PI**

<b>Crimping Force (ton)</b>	110	110	110
<b>Max. Capacity 1-2 Wire Braided (in)</b>	1	1	1
<b>Max. Capacity 4 Spiral (in)</b>	NA	NA	NA
<b>Max. Capacity 6 Spiral (in)</b>	NA	NA	NA
<b>Max. Capacity Industrial (in)</b>	NA	NA	NA
<b>Power</b>	Hand or Air	Hand	Air
<b>Max. Opening with Dies (mm / in)</b>	49 / 1.93	49 / 1.93	49 / 1.93
<b>Page Number</b>	5	6	7



**KC1-H64PM**



**KD165**



**KC2-J67**

<b>Crimping Force (ton)</b>	132	62	190
<b>Max. Capacity 1-2 Wire Braided (in)</b>	1 1/2	1 1/4	1 1/2
<b>Max. Capacity 4 Spiral (in)</b>	1 1/4*	1 1/4**	1 1/4*
<b>Max. Capacity 6 Spiral (in)</b>	NA	NA	NA
<b>Max. Capacity Industrial (in)</b>	NA	NA	NA
<b>Power</b>	Hand	1 HP (110 V)	1.5 HP (110 V)
<b>Max. Opening with Dies (mm / in)</b>	69 / 2.72	NA	NA
<b>Page Number</b>	8	9	10

\* 1 1/4" up to 4,000 PSI, 1" up to 5,000 PSI

\*\* 1 1/4" up to 3,000 PSI, 1" up to 4,000 PSI

Because we continually examine ways to improve our products, we reserve the right to alter specifications or discontinue products without prior notice.